

**Apply with
Confidence.**

CONBOND C5800
Contact Adhesive

Comply With VOC Rules.

Build With CONBOND.



VOC regulations shouldn't stop you from bonding with adhesive's most trusted brand. CONBOND C5800 aerosol and spray canister contact adhesive offers easy application, high performance and full compliance with SCQAMD and Bay Area VOC requirements.

SAFE & COMPLIANT

Contains No Chlorinated Solvents
Does Not Contain Ozone-Depleting Compounds

SUPERIOR PERFORMANCE

High Bond Strength
Aggressive Grab Tack

CONVENIENT

Available in Self-Contained Portable Canister Spray System
RETURNABLE CANISTERS AVAILABLE IN ALL SIZES
No Additional Equipment Needed. No Set Up or Clean Up Required

SUPPORT

Technical and Customer Support Mon-Fri, 8-5 ET.
24/7 MSDS and Technical Data Sheets at www.itwtacc.com

Available Through:

CONBOND C5800 PHYSICAL PROPERTIES

VOC Content: <80.0 grams/liter (EPA Method 24)
Dry Time: 2-5 minutes
Open Time: Up to 30 minutes
Spray Pattern (canister only): Pebble spray
Color: Clear or Green
Sizes: 14#, 27# and 270# returnable canisters; 27# disposable canister; 5 gallon pail; 55 gallon drum

CONBOND[®]

Made in the U.S.A by

ITW TACC

Rockland, Mass.

Phone 1-800-503-6991 Fax 1-800-231-8222
info@itwtacc.com www.itwtacc.com

ITW TACC, a division of Illinois Tool Works, is the world's leading manufacturer of high performance adhesives for professional and industrial use. Its brands are trusted worldwide in woodworking, construction, HVAC, roofing, manufactured housing, transportation and marine.