



# MATERIAL SAFETY DATA SHEET HIGH PRESSURE LAMINATE CHEMARMOR®

## SECTION I - PRODUCT INFORMATION

**PRODUCT NAME:**

Nevamar® ChemArmor Decorative Laminate

**CHEMICAL NAME:**

Laminated Plastic

**CHEMICAL FORMULA:**

Not Applicable Due to Composite Nature of Product

**CHEMICAL FAMILY:**

Plastic Composite

**PRODUCT USE:**

Decorative Surface Covering with Chemical Resistant Properties

**MANUFACTURER'S NAME AND ADDRESS:**

NEVAMAR COMPANY, LLC  
One Nevamar Place  
Hampton, South Carolina 29924

**CONTACT INFORMATION:**

Customer Service  
(803) 943-7200

**EMERGENCY TELEPHONE NUMBER:**

Chemtrec (800) 424-9300

## SECTION II - HAZARDOUS COMPONENTS

COMPONENT (C.A.S. Registry Number)	WEIGHT PERCENT	OSHA PEL	ACGIH TLV
---------------------------------------	-------------------	-------------	--------------

No hazardous components according to 29 CFR 1910.1200.  
Nuisance dust may be generated during cutting or sanding operations.

Nuisance dust is considered as "Particulates Not Otherwise Classified" or "Particulates Not Otherwise Regulated".

	OSHA PEL	ACGIH TLV
Particulates Not Otherwise Classified or Regulated	--- TWA 15 mg/m3 (Total Dust) STEL None	TWA 10 mg/m3 (Inhalable Particulate) STEL None
Particulates Not Otherwise Classified or Regulated	--- TWA 5 mg/m3 (Respirable Particulate) STEL None	TWA 3 mg/m3 STEL None



# MATERIAL SAFETY DATA SHEET HIGH PRESSURE LAMINATE CHEMARMOR®

## SECTION III - PHYSICAL PROPERTIES

### APPEARANCE AND ODOR:

Laminate sheet. No discernible odor.

### MOLECULAR WEIGHT:

Not applicable due to composite nature of product.

### SPECIFIC GRAVITY:

1.2 @ 70 F

### SOLUBILITY IN WATER:

Insoluble in water.

### pH:

Not applicable as product is solid.

## SECTION IV - FIRE AND EXPLOSION DATA:

### FLASH POINT:

Product has no flashpoint per Pensky Martins Closed Cup method.

### FIRE EXTINGUISHING MEDIA:

This material is considered a "Class A" type combustible material. Use water, foam or dry chemical to extinguish.

### FLAMMABLE LIMITS:

LOWER: None

UPPER: None

### SPECIAL FIRE FIGHTING PROCEDURES:

No special procedures required.

### UNUSUAL FIRE AND EXPLOSION HAZARDS:

Minimize accumulation of dust from cutting or sanding operations through use of local ventilation systems. High airborne concentrations of combustible dusts may be explosive if contacted with an ignition source.

### HAZARDOUS COMBUSTION PRODUCTS:

Thermal decomposition may release toxic and/or hazardous gases.



# MATERIAL SAFETY DATA SHEET HIGH PRESSURE LAMINATE CHEMARMOR®

## SECTION V - REACTIVITY DATA

### STABILITY:

Product is stable.

### CONDITIONS TO AVOID:

Avoid exposure to open flame.

### HAZARDOUS DECOMPOSITION PRODUCTS:

Thermal decomposition may release toxic and/or hazardous gases.

### HAZARDOUS POLYMERIZATION:

Will not occur.

## SECTION VI - HEALTH HAZARD INFORMATION

### EXPOSURE FROM ROUTINE USE:

Dust from cutting or sanding operations can cause irritation to the eyes, respiratory system and skin.

### EFFECTS OF OVEREXPOSURE:

Exposure to elevated dust levels may cause irritation to the eyes and respiratory system. Prolonged skin exposure to dust may cause drying of the skin.

### ROUTES OF EXPOSURE:

Potential routes of exposure are inhalation as well as skin and eye contact.

### EMERGENCY FIRST AID PROCEDURES:

EYE CONTACT: Wash eyes immediately with large amounts of water, occasionally lifting upper and lower lids, until no evidence of dust remains (approximately 15 - 20 minutes).

SKIN CONTACT: Wash affected area with soap and water to remove residual dust.

INHALATION: Remove from exposure to fresh air immediately.

INGESTION: Treat symptomatically and supportively if dust is ingested.

### OTHER:

The resin used to make this plastic contains small amounts of formaldehyde. The cured plastic may emit small amounts of formaldehyde during fabrication or if heating of the product occurs. Air testing of representative fabrication operations indicates that formaldehyde releases are minimal and formaldehyde air concentrations are below regulatory standards. Formaldehyde has been identified as a skin sensitizer in low concentrations and as a probable human carcinogen (IARC-2A, pharyngeal cancer excess in formaldehyde exposed workers).



# MATERIAL SAFETY DATA SHEET HIGH PRESSURE LAMINATE CHEMARMOR®

## SECTION VII - TOXICITY DATA

ORAL:	No data available.
DERMAL:	No data available.
INHALATION:	No data available.
EYE:	No data available.
CARCINOGENICITY:	Product has not been tested for carcinogenicity.

## SECTION VIII - SPECIAL PROTECTION INFORMATION

### WORK AND HYGIENE PRACTICES:

Wear safety glasses or goggles in fabrication operations that may generate airborne dust. Wear gloves during exposure to dust or frequently wash hands to remove residual dust. Maintain airborne dust limits below the exposure limits. Minimize dust generation and accumulation from fabrication operations. Sweep up dust. Avoid blowing dust with compressed air. Avoid exposure of dust to open flame and ignition sources. Electrically ground and bond all equipment used for fabrication operations.

### STORAGE AND HANDLING PRACTICES:

No special requirements for the products. Store dust away from heat, ignition sources and oxidizing agents.

### PROTECTIVE PRACTICES DURING MAINTENANCE OF CONTAMINATED EQUIPMENT:

Do not use compressed air to remove dust from equipment. Sweep or wash dust from unit.

### VENTILATION AND ENGINEERING CONTROLS:

Provide adequate general and local exhaust ventilation to maintain airborne concentrations below the exposure limits. Enclose fabrication operations, where possible, to minimize dust dispersion into other work areas.

### RESPIRATORY PROTECTION:

Where dust exposures may exceed the regulatory standards, respirators should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respirator protection (Z88.2-1992).

### EYE PROTECTION:

Wear ANSI-approved safety glasses or goggles in fabrication operations that may generate airborne dust.

### HAND AND BODY PROTECTION:

To prevent drying of skin, wear gloves during exposure to dust or frequently wash hands to remove residual dust. Use hand lotion to moisten hands.



# MATERIAL SAFETY DATA SHEET HIGH PRESSURE LAMINATE CHEMARMOR®

## SECTION IX - SPILL, LEAK AND DISPOSAL PROCEDURES

### IN CASE MATERIAL IS SPILLED OR RELEASED:

This material is a non-hazardous waste. Dispose of dust or excess material according to applicable federal, state and local regulations.

## SECTION X - REGULATORY INFORMATION

DOT: Product not regulated by D.O.T.

Additional Requirements for State of California: Warning: Decorative laminate products contain formaldehyde, a substance known to the State of California to cause cancer. Laminates contain small amounts of residual formaldehyde that may be released in measureable quantities when stored in bulk quantities.

MSDS NUMBER: HPNLP  
Document Number: N2004-1  
Updated: 02/04  
Supersedes: 05/03

**IMPORTANT:** The information and data contained herein are believed to be accurate and have been compiled from sources believed to be accurate. All information contained herein is offered for your consideration, information, investigation and verification. NEVAMAR COMPANY MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, CONCERNING THE ACCURACY OR COMPLETENESS OF THE INFORMATION AND DATA HEREIN. THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE SPECIFICALLY EXCLUDED. Nevamar Company will not be responsible for claims related to any parties' use of or reliance on information and data contained herein regardless of whether it is claimed that the information are inaccurate, incomplete, or otherwise misleading.