

MSDS Material Safety Data Sheet

Wilsonart International



WILSONART® PVA Wood Glue Series

Page 1 of 6

MSDS Number: 19023

Revision Date: 8/25/2005

1 PRODUCT AND COMPANY IDENTIFICATION

Common Name WILSONART® PVA Wood Glue Series

Includes:

WILSONART® 10 Adhesive

WILSONART® 20 Adhesive

WILSONART® Type II Adhesive

MANUFACTURER WILSONART INTERNATIONAL, INC.
P.O. BOX 6110 - 2400 WILSON PLACE
TEMPLE, TX 76503
INFORMATION PHONE: 800-433-3222 (USA)

Trade Name WA PVA Wood Glue

MATERIAL USES Adhesive for laminate

Revision # NEW

In Case of Emergency Contact:

CHEMTREC: 800-424-9300 (USA)
703-527-3887 (INTERNATIONAL)

2 COMPOSITION/INFORMATION ON INGREDIENTS

Name	CAS#	% by weight
Polyvinyl alcohol (10 and 20)	9002-89-5	5 - 15
Vinyl acetate polymer (10 and 20)	9003-20-7	10 - 50
Vinyl acetate polymer (Type II)	NJTSRN 990010	40 - 60
Water (10, 20, Type II)	7732-18-5	15 - 70
Aromatic diester (10 and 20)	NJTSRN 950001	1 - 5

MSDS Material Safety Data Sheet

Wilsonart International



WILSONART® PVA Wood Glue Series

Page 2 of 6

MSDS Number: 19023

Revision Date: 8/25/2005


3 HAZARDS IDENTIFICATION

Route of Entry: Skin, eyes, and respiratory tract.
Target Organs: None.
Inhalation: Breathing vapors may cause irritation to the respiratory tract.
Skin Contact: May cause skin irritation.
Eye Contact: May cause eye irritation
Ingestion: Not an expected route of entry. If ingested it may cause irritation to gastro-intestinal tract.

HMIS (United States):

HEALTH	1
FLAMMABILITY	0
REACTIVITY	0
PPE	B

NFPA (United States):



WHMIS (Canada): D2A.



4 FIRST AID MEASURES

Inhalation: Remove patient to fresh air. If patient is having difficulty breathing seek immediate medical attention. If not breathing, clear airway and start mouth-to-mouth artificial respiration (or use bag-mask respirator). Get immediate medical attention.
Skin Contact: Wash affected areas with soap and water. If irritation persist, seek medical attention.
Eye Contact: Flush eyes with water for 15 minutes. Remove contact lenses prior to water flush. Seek medical attention.
Ingestion: Give patient 3 - 4 glasses of water. DO NOT induce vomiting. Get immediate medical attention. DO NOT give anything by mouth to an unconscious person.

5 FIRE FIGHTING MEASURES

Flash Point: Not Applicable.
Flash Point Method: Not Applicable.
Autoignition Temperature: Not Applicable.

Material is not flammable. Dry adhesive will burn.

In case of fire use dry chemical or CO₂ extinguishing media.

Use extinguishing media appropriate for surrounding materials.

Wear self contained breathing apparatus and protective gear suitable for surrounding materials.

Hazardous decomposition products include carbon oxides (CO, CO₂) and acetic acid.

6 ACCIDENTAL RELEASE MEASURES

Personal precautions:

Wear appropriate PPE. Make sure work area is well ventilated. Spilled adhesive may be slippery.

Environmental precautions:

Keep out of sewers or drains.

Clean-up methods

Dike and contain spill. Absorb spilled product with vermiculite, dry sand, or earth. Dispose in a suitable container.

7 HANDLING AND STORAGE

Handling Precautions: Avoid breathing vapors. Handle in well ventilated areas. Wash hands after handling with soap and water.

Storage Requirements: Avoid freezing and boiling temperatures. Minimize contact with atmospheric air to prevent inoculation with microorganisms.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: Use in a well ventilated area.

Protective Equipment: Wear approved safety glasses with side shields. Wear latex gloves. Wear normal work clothing. Ensure a functioning eye wash is either in or near the work area.

Exposure Guidelines/Other:

<u>Ingredient Name</u>	<u>Exposure Limits</u>
Vinyl acetate monomer	OSHA PEL: 10 ppm; ACGIH TLV 10 ppm STEL 20ppm

Consult local authorities and local regulations for exposure limits.

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance: White mobile liquid.

Physical State: Liquid.

Odor: Mild Sweet.

pH: 4 - 5 (10 and 20); 2.42 (Type II)

Vapor Pressure: Equivalent to water.

Vapor Density: Equivalent to water.

Boiling Point: Similar to water.

Freezing/Melting Pt.: Similar to water.

Solubility: Soluble.

Spec Grav./Density: 1.094 (10 and 20); 1.07 (Type II)

VOC: < 20g/L

Viscosity: 4750 cps (10 and 20); 5500 cps (Type II)

10 STABILITY AND REACTIVITY

Stability: Stable as supplied. Coagulation may occur following freezing/thaw cycle or boiling.

Conditions to avoid: Extreme temperatures.

Materials to avoid (incompatibility): Copper and copper alloys, strong acids, and alkalis.

MSDS Material Safety Data Sheet

Wilsonart International



WILSONART® PVA Wood Glue Series

Page 4 of 6

MSDS Number: 19023

Revision Date: 8/25/2005

Hazardous Decomposition products: Carbon oxides (CO₂, CO) and acetic acid.

Hazardous Polymerization: Will not polymerize.

11 TOXICOLOGICAL INFORMATION

Acute Toxicity:

None reported.

Chronic toxicity:

All

These products may contain trace amounts of vinyl acetate monomer (VAM) and ACGIH evaluates VAM as an A3-Animal Carcinogen. Available evidence suggests that VAM is not likely to cause cancer in humans except under uncommon or unlikely routes of exposure, but because VAM can be metabolized to acetaldehyde, which has an IARC 2B classification (possibly carcinogenic to humans), these products have also been listed under IARC Category 2B.

12 ECOLOGICAL INFORMATION

Ecotoxicity	Not available.
BOD5 and COD	Not available.
Biodegradable/OECD	Not available.
Mobility	Not available.

Toxicity of the Products of Biodegradation	Not available.
--	----------------

Special Remarks on the Products of Biodegradation	No additional remark.
---	-----------------------

13 DISPOSAL CONSIDERATIONS

Dispose of in accordance with Federal, State, and local regulations.

14 TRANSPORT INFORMATION

DOT Classification - Resin Compound - Not DOT Regulated//Keep from freezing

Proper Shipping Name - Adhesive Resin Compound

Markings - None

Packaging instructions - Keep from freezing

Marine Pollutant - NO

TDG hazard class - None

15 REGULATORY INFORMATION

U.S. Federal Regulations

OSHA (29 CFR 1910.1200) - Vinyl acetate.

CERCLA Rq

Vinyl acetate monomer 5000 lbs.

MSDS Material Safety Data Sheet

Wilsonart International



WILSONART® PVA Wood Glue Series

Page 5 of 6

MSDS Number: 19023

Revision Date: 8/25/2005

Acetaldehyde 1000 lbs.

TSCA inventory: The chemicals in this product are listed.
SARA 302/304/311/312 extremely hazardous substances: None.
SARA 302/304 emergency planning and notification: None.
SARA 302/304/311/312 hazardous chemicals: None.
SARA 311/312 MSDS distribution, chemical inventory, hazard identification: None.
SARA 313 toxic chemical notification and release reporting: None.
CWA 307: None.
CWA 311: None.
CAA 112 accidental release prevention: None.
CAA 112 regulated flammable substances: None.
CAA 112 regulated toxic substances: None.

International Regulations

EINECS - Chemicals are listed.
DSL - R36/37 - Irritating to eyes and respiratory system.
WHIMS - D2A.

State Regulations

Pennsylvania RTK: Vinyl acetate, acetaldehyde.
Minnesota RTK: Vinyl acetate, acetaldehyde.
Massachusetts RTK: Vinyl acetate, acetaldehyde.
New Jersey RTK: Vinyl acetate, acetaldehyde.
Rhode Island RTK: Vinyl acetate, acetaldehyde.
California Prop. 65:
Warning. This product may contain trace amounts of vinyl acetate monomer, acetaldehyde and formaldehyde, chemicals known to the State of California to cause cancer or reproductive toxicity.

16

OTHER INFORMATION

References

Lewis, R. J., Rapid Guide to Hazardous Chemicals in the Workplace, 4th ed., Wiley-Interscience, New York, 2000.
NIOSH Pocket Guide to Chemical Hazards, Department of Health and Human Services, National Institute for Occupational Safety and Health, 2004.
TLVs and BEIs, Threshold Limit Values for Chemical Substances and Physical Agents & Biological Exposure Agents, ACGI Worldwide, Cincinnati, 2003.

Glossary

ACGIH - American Conference of Governmental Industrial Hygienists
ASTM - American Society for Testing and Materials
ADR - Agreement on Dangerous Goods by Road (Europe)
BOD5 - Biological Oxygen Demand in 5 days
CAA - Clean Air Act
CAS - Chemical Abstracts Services
CEPA - Canadian Environmental Protection Act
CERCLA - Comprehensive Environmental Response, Compensations and Liability Act
CFR - Code of Federal Regulations
CWA - Clean Water Act

MSDS Material Safety Data Sheet

Wilsonart International



WILSONART® PVA Wood Glue Series

Page 6 of 6

MSDS Number: 19023

Revision Date: 8/25/2005

DOT - Department of Transportation
DSCL - Dangerous Substances Classification and Labeling (Europe)
DSL - Domestic Substance List (Canada)
EEC/EU - European Economic Community/European Union
EINECS - European Inventory of Existing Commercial Chemical Substances
HCS - Hazard Communication System
HMIS - Hazardous Material Information System
IARC - International Agency for Research on Cancer
LD50/LC50 - Lethal Dose/Concentration kill 50%
LDLo/LCLo - Lowest Published Lethal Dose/Concentration
NFPA - National Fire Prevention Association
NIOSH - National Institute for Occupational Safety & Health
NTP - National Toxicology Program
OSHA - Occupational Safety & Health Administration
PEL - Permissible Exposure Limit
RCRA - Resource Conservation and Recovery Act
SARA - Superfund Amendments and Reorganization Act
STEL - Short Term Exposure Limit (15 minutes)
TDG - Transportation of Dangerous Goods (Canada)
TLV-TWA - Threshold Limit Value-Time Weighted Average
TSCA - Toxic Substances Control Act
WHMIS - Workplace Hazardous Material Information System

CHEMTREC:
800-424-9300 (USA)
703-527-3887 (International)

Notice to Reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named manufacturer nor any of its subsidiaries assumes any liability whatsoever for accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

END OF MSDS DOCUMENT